



(12) **United States Patent**
Sahashi

(10) **Patent No.:** **US 9,409,506 B2**
(45) **Date of Patent:** **Aug. 9, 2016**

(54) **CONVEYANCE SEAT**

(56) **References Cited**

(71) Applicant: **TOYOTA BOSHOKU KABUSHIKI**
KAISHA, Aichi-ken (JP)

(72) Inventor: **Hideo Sahashi**, Aichi-ken (JP)

(73) Assignee: **TOYOTA BOSHOKU KABUSHIKI**
KAISHA, Aichi-Ken (JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

U.S. PATENT DOCUMENTS

3,273,877	A *	9/1966	Geller et al.	267/89
3,833,454	A *	9/1974	Ambrose	297/452.57
5,647,635	A	7/1997	Aumond et al.	
5,893,579	A	4/1999	Kimura et al.	
7,669,929	B2	3/2010	Simon et al.	
7,871,126	B2	1/2011	Becker et al.	
8,240,759	B2 *	8/2012	Hobl et al.	297/218.1
8,919,878	B2 *	12/2014	Sakamoto	297/218.2

(Continued)

FOREIGN PATENT DOCUMENTS

CN	101362445	2/2009
CN	102673454	9/2012
DE	3001429	7/1980

(Continued)

OTHER PUBLICATIONS

Germany Office action, dated Dec. 3, 2014 along with an English translation thereof.

(Continued)

(21) Appl. No.: **14/494,725**

(22) Filed: **Sep. 24, 2014**

(65) **Prior Publication Data**

US 2015/0091361 A1 Apr. 2, 2015

(30) **Foreign Application Priority Data**

Sep. 30, 2013 (JP) 2013-203663

(51) **Int. Cl.**

A47C 7/02	(2006.01)
B60N 2/72	(2006.01)
B60N 2/58	(2006.01)
B60N 2/68	(2006.01)
B60N 2/70	(2006.01)

(52) **U.S. Cl.**

CPC .. **B60N 2/72** (2013.01); **B60N 2/58** (2013.01);
B60N 2/5816 (2013.01); **B60N 2/68** (2013.01);
B60N 2/70 (2013.01)

(58) **Field of Classification Search**

CPC A47C 7/40; A47C 31/02; A47C 7/185;
B60N 2/72; B60N 2/58; B60N 2/5816;
B60N 2/70

USPC 297/218.3, 452.59, 452.57
See application file for complete search history.

Primary Examiner — Laurie K Cranmer

(74) *Attorney, Agent, or Firm* — Greenblum & Bernstein P.L.C.

(57) **ABSTRACT**

A conveyance seat includes: a seat frame; a seat pad that covers the seat frame; and a seat cover that covers the seat pad and that is fixed to the seat frame. The seat pad has a U-shaped portion formed by a supporting portion, a side surface portion that is continuous with the supporting portion, and a tension adjusting portion that is continuous with the side surface portion, the tension adjusting portion having a protruding portion as a portion of the tension adjusting portion that protrudes toward the seat cover. The protruding portion abuts against the seat cover.

20 Claims, 3 Drawing Sheets

